

## Technical data


Version		60 4/8	60 8/16	60 14/28	140 4/8	140 8/16	140 14/28	200 14/28
Rated voltage	V DC	24 - 60	24 - 60	24 - 60	60 - 140	60 - 140	60 - 140	100-200
Rated current	A	4	8	14	4	8	14	14
Peak current	A	8	16	28	8	16	28	28
Undervoltage	V DC	20	20	20	40	40	40	58
Overvoltage	V DC	84	84	84	182	182	182	275

### General technical data for all versions

Max. speed	rpm	5000
Minimum tacho voltage	V DC	5
Operating temperature	°C	0 - 40
Max. humidity	%	80
Weight	kg	0.51
Speed setpoint		Differential +/-10 V (input resistance 20 kOhm)
Temperature drift, differential stage		+/-18 µV/°C (max.)
Temperature drift, differential controller		+/-18 µV/°C (max.)
Input/output current request		+/-10 V (input resistance 47 kOhm)
Release signal		+10/30 V (input resistance 10 kOhm)
Motor short-circuit protection		yes
Overvoltage protection for intermediate circuit		yes
Motor overload protection		yes
Protection in case of wire breakage		yes
RoHs / REACH		yes
EMC-tested		no



## Pin assignment without card holder, 32-pin

Manufacturer code: 86094647113755ELF




1a	-	17a	-	1c	Reference potential 0V	17c	(+) Power supply input
2a	-	18a	-	2c	Status - output	18c	-
3a	-	19a	-	3c	Current request	19c	(-) Power supply input
4a	-	20a	-	4c	-10V (max. 5 mA)	20c	(-) Power supply input
5a	-	21a	-	5c	+10V (max. 5 mA)	21c	(-) Power supply input
6a	-	22a	-	6c	(+) Setpoint input	22c	(-) Power supply input
7a	-	23a	-	7c	Release (+10/30 V DC)	23c	-
8a	(-) Setpoint input	24a	-	8c	(+) Tacho input	24c	(+M) Motor connection
9a	-	25a	-	9c	(-) Tacho input	25c	(+M) Motor connection
10a	-	26a	-	10c	-	26c	(+M) Motor connection
11a	Current monitor (+/-8V)	27a	-	11c	-	27c	(+M) Motor connection
12a	CHB encoder input	28a	-	12c	CHA encoder input	28c	-
13a	-	29a	-	13c	-	29c	(-M) Motor connection
14a	-	30a	-	14c	(+) Power supply input	30c	(-M) Motor connection
15a	-	31a	-	15c	(+) Power supply input	31c	(-M) Motor connection
16a	-	32a	-	16c	(+) Power supply input	32c	(-M) Motor connection

## Pin assignment with card holder, 17-pin and 2-pin




0	Current monitor (+/-8V)	5	+10V (max. 5 mA)	9	(+) Tacho input	13	(-) Power supply input
1	Status - output	6	Release (+10/30 V DC)	10	(-) Tacho input	14	(-) Power supply input
2	Current request	7	(+) Setpoint input	11	(+) Power supply input	15	(+M) Motor connection
3	Reference potential 0V	8	(-) Setpoint input	12	(+) Power supply input	16	(-M) Motor connection
4	-10V (max. 5 mA)						
1.1	CHA encoder input	1.2	CHB encoder input				

## Controller dimensions (Eurocard format)



## Controller dimensions (Eurocard format)



The drawings and data in this document are provided as general information for our customers. For specific use cases, a separate quotation must be requested. Kern Antriebstechnik GmbH accepts no responsibility for any errors found in the respective datasheets. Kern Antriebstechnik GmbH reserves the right to make changes to its products without prior notice. This also applies to products currently available on the market, provided that – unless otherwise specified – the modification in question does not restrict the product's usability. All goods and trademarks mentioned in this datasheet are the property of Kern Antriebstechnik GmbH.